

SAFETY DATA SHEET <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;"> Coburn Chemicals, Inc 410-666-5227 </div>	DEAD SEA WORKS LTD Potash House, P.O.Box 75, Beer-Sheva 84100 Israel MARKETING DIVISION CHEMICAL PRODUCTS TEL: +972-8-6465347; FAX: +972-8-6280533
	Trade Name: MAG Pellets

Section 1: Product and Company identification

Commercial Product Name: MAG Pellets
 CAS: (Magnesium chloride) 7791-18-6
 Manufacturer: Dead Sea Work LTD
 P.O.B Beer Sheva 84100, Israel
 Tel: +972-8-6465347
 Fax: +972-8-6280533
 www.dsosalts.com

Section 2: Composition/Information on Ingredients

Appearance: White flakes odorless soluble in water

Chemical name	CAS-No	EINECS-No	Concentration %	Classification
Magnesium Chloride	7791-18-6	-	46.5-47.5	-
Calcium Chloride	10043-52-4	233-140-8	2-2.2	R36, Xi
Sodium Chloride	7647-14-5	231-598-3	0.5-0.8	-
Potassium Chloride	7447-40-7	231-211-8	0.2-0.5	-
Water of crystalization	7732-18-5	231-791-2	Balance	-

(See full text of R-phrases in chapter 16.)

Section 3: Hazards Identification

May be irritating to eyes and respiratory system.

Not classified as hazardous material.

Section 4: First - Aid Measures

Symptoms: This substance is not considered toxic or dangerous, though care should be taken during use and any questions referred to medical personnel

Skin contact: The substance is not dangerous. However, over exposure or contact with open wounds may cause slight irritation

Eyes contact: Wash with water for at least 15 minutes (open eyes).

Ingestion: Do not induce vomiting. The substance is not dangerous. Obtain medical attention.

Inhalation: The substance is not dangerous by inhalation.

SAFETY DATA SHEET	DEAD SEA WORKS LTD Potash House, P.O.Box 75, Beer-Sheva 84100 Israel MARKETING DIVISION CHEMICAL PRODUCTS TEL: +972-8-6465347; FAX: +972-8-6280533
	Trade Name: MAG Pellets Page 2 of 5

Section 5: Fire-Fighting Measures

Fire: Non-combustible

Suitable extinguishing media: Use any means suitable for extinguishing surrounding fire

Extinguishing media that must not be used for safety reasons: None

In the event of a fire, wear full protective clothing and a self-contained breathing apparatus.

Section 6: Accidental Release Measures

Avoid contamination of water sources.

Pick up mechanically and dispose according to point 13. Minor residues to be washed away with excessive water flow. If spilling occurs on public highway, wash toughly with water and absorbent should be applied (i.e. sand) to prevent skidding on a slippery surface. Dispose of wastewater according to regulations.

Section 7: Handling and Storage

Keep away from incompatible materials (see section 10).

Safety phrases

S22: Do not breathe dust.

S25: Avoid contact with eyes.

Prevent contact with water or humid atmosphere.

Keep bags tightly closed and dry.

Section 8: Exposure Control / Personal Protection

Threshold values: Not available

Personal Protective equipment: Generally, personal protection is a function of exposure. It is recommended to use working shoes, working clothes or lab coat. Working should be done in a well-ventilated area. In addition: Dust mask under strong dust development, full protective gear includes: protective cloth, boots, rubber gloves and breathing apparatus- according to the level of exposure.

Respiratory protection: If the exposure limit is exceeded and engineering controls are not feasible, use particulate respirator.

In case of an emergency: Full protective gear and a self-contained breathing apparatus should be used, according to the severity.

SAFETY DATA SHEET	DEAD SEA WORKS LTD Potash House, P.O.Box 75, Beer-Sheva 84100 Israel MARKETING DIVISION CHEMICAL PRODUCTS TEL: +972-8-6465347; FAX: +972-8-6280533
	Page 3 of 5
Trade Name: MAG Pellets	

Section 9: Physical and Chemical Properties

General information:

Form: Flakes

Color: white

Boiling point °C: N/A

Melting point °C: N/A

Density gr/cm³: 1.6 in 20°C

Change in physical state: Hygroscopic

Vapor density (air=1): N/A

Vapor pressure (mm Hg): N/A

Solubility (in water): 167 g/100 ml water

pH: 8.2, at 10% in aqueous solution

Bulk density: 800-900 kg/m³

Flash point °C: Non-flammable

Auto-ignition temperature °C: N/A

LEL: N/A **UEL:** N/A

Viscosity: N/A

Section 10: Stability and Reactivity

Hazardous polymerization: Will not occur.

Chemical reactivity: Stable under ordinary conditions. Hygroscopic. May react with oxidizing agents.

Hazardous decomposition products: Oxides of: potassium, calcium, magnesium and sodium, and above 160°C decomposes giving HCl gases

Section 11: Toxicological Information

Acute toxicity by manufacture:

LD50 (oral rat) 8100 mg/kg

Magnesium Chloride:

LD50 (oral rat) 2800 mg/kg

Calcium Chloride:

LD50 (oral rat) 1000 mg/kg

LD50 (oral mouse) 1940 mg/kg

Sodium Chloride:

LD50 (oral rat) 3000 mg/kg

LD50 (absorption through skin rabbit) 10000 mg/kg

LC50 (inhalation rat) 42000 mg/m³ (60 minutes)

SAFETY DATA SHEET	DEAD SEA WORKS LTD Potash House, P.O.Box 75, Beer-Sheva 84100 Israel MARKETING DIVISION CHEMICAL PRODUCTS TEL: +972-8-6465347; FAX: +972-8-6280533
	Page 4 of 5
Trade Name: MAG Pellets	

Potassium Chloride:

LD50 (oral rat) 2600 mg/kg

LD50 (oral mouse) 383 mg/kg

LD50 (intraperitoneal rat) 660 mg/kg

LDLo (intraperitoneal dog) 85 mg/kg

Section 12: Ecological Information

Environmental hazards: If properly introduced in small concentrations into adapted biological sewage treatment plants, decomposition of the activated sludge is not affected.

Not mentioned in the EC Regulations of 4/5/76 concerning discharge of dangerous materials into waters, neither in List I nor List II.

MgCl₂ is a component of seawater

Biodegradability: No data available.

Section 13: Disposal Considerations

Dispose of in accordance with local regulations.

Contaminated Packaging: Contaminated bags should be emptied thoroughly; after proper cleaning they can be recycled.

Section 14: Transport Information

Non-hazardous for air, sea and road transportation.

Section 15: Regulatory Information

Labeling in accordance with EC directives: No specific marking required according to EC-Regulations 67/548

R-phrases: Not available

S-phrases:

S22: Do not breathe dust.

S25: Avoid contact with eyes.

SAFETY DATA SHEET	DEAD SEA WORKS LTD Potash House, P.O.Box 75, Beer-Sheva 84100 Israel MARKETING DIVISION CHEMICAL PRODUCTS TEL: +972-8-6465347; FAX: +972-8-6280533
Trade Name: MAG Pellets	Page 5 of 5

Section 16: Other Information

Full text of R-phrases with No. appearing in section 2:
R36: Irritating to eyes.

NFPA Ratings: Health: **1** Flammability: **0** Reactivity: **0**

Date of issue: 30TH October 2005

According to Commission Directive 2001/59/EC

The information herein is based on the present state of our knowledge. It is believed to be correct but is not necessarily all-inclusive and shall be used only as a guide. DEAD SEA WORKS Ltd, and Haz-Mat Ltd. shall not be held liable for any damage resulting from handling or from contact with the above product. For further information, contact DEAD SEA WORKS Ltd or Haz-Mat Ltd .

